

Manufactured from high density polyethylene (HDPE), Ridgiduct Power offers a stiff, yet flexible, twinwall cable protection system that is light in weight and robust. Ridgiduct Power Class 3 is a 94mm- diameter black duct that complies with ENATS 12-24 Class 3 performance requirements, although it is a non-standard size.



Key benefits

- Complies with ENATS 12-24 Class 3 performance requirements (non-standard size), 450N compressive strength at 23°C
- Complies with BS EN 61386-24: 2010, Type 450N normal duty impact resistance
- Network Rail PADS approved
- Supplied with an integral coupler
- IP4X system (dust protection)
- Low weight, flexible, durable and high strength
- Good impact resistance, even at low temperatures
- Available in an alternative twinwall split duct form, for easy installation around existing cables with minimal change in strength



RIDGIDUCT POWER CLASS 3 DUCT & COUPLINGS

ID (mm)	OD (mm)	LENGTH (m)	PRODUCT CODE	DUCT QTY	COUPLING CODE	COUPLING QTY
94	110	6*	RB94X6SP**	95***	RBC94****	10

* Also available in 5.8m lengths (amend duct code to RB94X5.8SP**).

** Made to order and subject to minimum order quantities and lead time.

*** Must be ordered in pack quantities.

**** Sealed system can be achieved using 2no Ridgidrain sealing rings (SRD94) & 1no Ridgidrain coupler (CRD94).

Technical Support

Detailed guidance and assistance is available.

For further information, please contact our Technical Team

on +44 (0)1509 615 100 or email: civils@polypipe.com

or visit www.polypipe.com/civils-technical-hub

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions and weights given are nominal and Polypipe may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on August 2019. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. © Polypipe is a registered trademark of Polypipe. All Polypipe products are protected by Design Right under CDPA 1988. Copyright © 2019 Polypipe. All rights reserved.

Polypipe Civils

Charnwood Business Park, Loughborough, Leicestershire LE11 1LE

Tel: +44 (0) 1509 615100 Fax: +44 (0) 1509 610215 Email: civils@polypipe.com

www.polypipe.com/civils